

TECHNICAL DATA SHEET



DESCRIPTION

Cotton gloves coated in ¾ with crinkled latex with a rough structure. Finished with a long, elastic welt, they guarantee an excellent grip on slippery dry and wet surfaces. A more natural shape ensures a better fit to the hand and increases work safety. Thanks to the partial coating of the back of the hand, the gloves guarantee air access, which increases their comfort of use. Stretchy even at low temperatures, they perfectly protect hands against sharp objects. They do not leave marks on the glass.

APPLICATIONS

Glass and ceramic industry, works in a wet environment, waste collection, agriculture and forestry, slippery plastics, work with a stream of steam, scaffolding.



EN 388:2016+A1:2018



Abrasion resistance Blade cut resistance Tear resistance Puncture resistance TDM cut resistance EN ISO 21420:2020





PPE regulation (EU) 2016/425 | EN ISO 21420:2020 General requirements for protective gloves | EN 388:2016+A1:2018 Protective gloves against mechanical risk

P.H.P.U. SEMEX Fertacz, Huszno Sp. J. ul. Jagiellońska 101/105,

ul. Jaglellonska 101/105, 42-202 Częstochowa, Poland tel.: +48 34 39 06 735 e-mail: bhp@semex.pl www.hfsafety.pl

CRACOW BRANCH

ul. Biskupińska 28, budynek X 30-732 Kraków tel.: +48 12 390 46 00 e-mail: bhp.krakow@semex.pl www.hfsafety.pl



2

