

TECHNICAL DATA SHEET



DESCRIPTION

Ultra-durable knitted gloves with high cut resistance (level D). Comfortable and lightweight (18 gauge) for a perfect fit. With their excellent air permeability parameters, they ensure breathability and ultimate comfort. Their ergonomic shape reduces hand fatigue and the nitrile coating guarantees maximum grip in wet, dry and oily environments. An additional coating between the index finger and thumb significantly increases the durability of the gloves. Thanks to the integrated Sanitized® hygiene function, they are protected against bacterial growth and unpleasant odours are reduced. This model is compatible with touchscreens.

APPLICATIONS

All work requiring precision and high manual efficiency, including: precision machines, mechanical assembly, workshops engineering, as well as the automotive industry, agriculture and construction.



EN388:2016



Abrasion resistance Blade cut resistance Tear resistance Puncture resistance TDM cut resistance



4

X 4 2

D

PPE regulation (EU) 2016/425 | EN420 General requirements for protective gloves | EN388 Protective gloves against mechanical risk

P.H.P.U. SEMEX Fertacz, Huszno Sp. J. ul. Jagiellońska 101/105 42-202 Częstochowa, Polska tel.: +48 34 39 06 735 e-mail: bhp@semex.pl www.hfsafety.pl

CRACOW BRANCH

ul. Biskupińska 28, budynek X 30-732 Kraków tel.: +48 12 390 46 00 e-mail: bhp.krakow@semex.pl www.hfsafety.pl



