

sensiCUT D

TECHNICAL SPECIFICATION

Type:	knitted
Material:	cut-resistant fibers
Coating:	nitrile
Cuff style:	elastic
Weight:	light
Colour:	blue, black
Sizes:	6, 7, 8, 9, 10, 11, 12



DESCRIPTION

Ultra-durable knitted gloves with high cut resistance (level D). Comfortable and lightweight (18 gauge) for a perfect fit. With their excellent air permeability parameters, they ensure breathability and ultimate comfort. Their ergonomic shape reduces hand fatigue and the nitrile coating guarantees maximum grip in wet, dry and oily environments. An additional coating between the index finger and thumb significantly increases the durability of the gloves, while the Sanitized® application provides anti-microbial protection. This model is compatible with touchscreens.

APPLICATIONS

All work requiring precision and high manual efficiency, including: precision machines, mechanical assembly, workshops engineering, as well as the automotive industry, agriculture and construction.



Abrasion resistance	4
Blade cut resistance	X
Tear resistance	4
Puncture resistance	2
TDM cut resistance	D

PPE regulation (EU) 2016/425 | EN420 General requirements for protective gloves | EN388 Protective gloves against mechanical risk

PH.P.U. SEMEX Fertac, Huszno sp. j.
ul. Jagiellońska 101/105,
42-200 Częstochowa, Poland
tel.: +48 34 39 06 735
e-mail: bhp@semex.pl
www.hfsafety.pl

ODDZIAŁ KRAKÓW
ul. Biskupińska 28, budynek X
30-732 Kraków
tel.: +48 12 390 46 00
e-mail: bhp.krakow@semex.pl
www.hfsafety.pl

