

flexyOIL

TECHNICAL DATAS

Type: knitted
 Coating: double, nitrile
 Material: polyester /stitch 13/
 Cuff: elastic
 Colour: orange, black
 Sizes: 7, 8, 9, 10, 11



RESISTANCE
TO CONVECTIVE
HEAT UP TO 100°C

EXCELLENT GRIP

MAXIMUM GRIP
IN OILY ENVIRONMENTS

DESCRIPTION

Knitted polyester gloves with a two-layer nitrile coating - ideal for light applications requiring a good grip in oily environments. They perfectly protect the skin from contact with industrial liquids, guaranteeing dry hands and comfort when working with oily objects.

APPLICATIONS

Automotive, machinery and equipment, chemical and petroleum industries; component assembly, maintenance work.



EN 388:2016+A1:2018



4131X

EN 388:2016+A1:2018

Mechanical risk
 Abrasion resistance 4
 Blade cut resistance 1
 Tear resistance 3
 Puncture resistance 1
 TDM cut resistance X

EN 407:2020



X1XXXX

EN 407:2020

Protection against thermal risks (heat and/or fire)
 Limited Flame Spread X
 Contact Heat 1
 Convective Heat X
 Radiant Heat X
 Small Splashes of Molten Metal X
 Large Quantities of Molten Metal X

EN ISO 21420:2020



CE CAT II

PPE regulation (EU) 2016/425 | EN 388:2016+A1:2018 - Mechanical risk | EN 407:2020 - Protection against thermal risks (heat and/or fire) | EN 21420:2020 - General requirements for protective gloves |

P.H.P.U. SEMEX Fertacz, Huszno Sp. J.

ul. Jagiellońska 101/105,
 42-202 Częstochowa, Poland
 tel.: +48 34 39 06 735
 e-mail: bhp@semex.pl
 www.hfsafety.pl

BRANCH KRAKÓW

ul. Biskupińska 28, budynek X
 30-732 Kraków
 tel.: +48 12 390 46 00
 e-mail: bhp.krakow@semex.pl
 www.hfsafety.pl

