

flexyOIL

TECHNICAL SPECIFICATION

Type:	knitted
Coating:	double, nitrile
Material:	polyester /stitch 13/
Cuff:	elastic
Colour:	orange, black
Sizes:	7, 8, 9, 10, 11

RESISTANCE TO CONVECTIVE HEAT UP TO 100°C



EXCELLENT GRIP

MAXIMUM GRIP
IN OILY ENVIRONMENTS

PROPERTIES

Knitted polyester gloves with a two-layer nitrile coating - ideal for light applications requiring a good grip in oily environments. They perfectly protect the skin from contact with industrial liquids, guaranteeing dry hands and comfort when working with oily objects.

APPLICATION

Automotive, machinery and equipment, chemical and petroleum industries; component assembly, maintenance work.



EN 407:2020 – Protection against thermal risks (heat and/or fire)

Limited Flame Spread	X
Contact Heat	1
Convective Heat	X
Radiant Heat	X
Small Splashes of Molten Metal	X
Large Quantities of Molten Metal	X



EN 388:2016+A1:2018 – mechanical risk

Abrasion resistance	4
Blade cut resistance	1
Tear resistance	3
Puncture resistance	1
ISO 13997 TDM	X



PPE regulation (EU) 2016/425 | EN ISO 21420:2020 General requirements for protective gloves
EN 388:2016+A1:2018 Gloves protecting against mechanical risks | EN 407:2020 Gloves protecting against heat and/or flame