

safeFIT

TECHNICAL SPECIFICATION

Type:	knitted
Coating:	PU
Material:	cut resistant yarn, 13 gg
Cuff:	flexible welt
Waga:	lightweight
Kolor:	grey
Rozmiary	6, 7, 8, 9, 10, 11



PROPERTIES

Gloves with excellent mechanical resistance characteristics. Made of cut-resistant knitted fabric, thanks to the polyurethane coating in the gripping area, they provide good grip. Finished with a long safety cuff. Well-fitting, suitable for works requiring dexterity and a good sense of touch.

APPLICATION

Ceramic and glass industries, as well as sectors involved in injection molding, automotive, and other industries using sharp-edged objects.



EN 388:2016+A1:2018



4X44D

EN 388:2016

Abrasion resistance	4
Blade cut resistance	X
Tear resistance	4
Puncture resistance	4
ISO 13997 TDM	D

EN 407:2020



X1XXXX

EN 407:2020

Limited Flame Spread	X
Contact Heat	1
Convective Heat	X
Radiant Heat	X
Small Splashes of Molten Metal	X
Large Quantities of Molten Metal	X

EN ISO 21420:2020



CAT II



PPE Regulation (EU) 2016/425 | EN ISO 21420:2020 – General requirements for protective gloves | EN 388:2016+A1:2018 – Mechanical risk | EN 407:2020 – Protection against thermal risks (heat and/or fire)