

## cutD PRO

### TECHNICAL DATAS

Type: knitted  
 Coating: PU  
 Fabric: cut-resistant yarn  
 Cuff style: elastic welt  
 Weight: lightweight  
 Colour: grey  
 Size: 6, 7, 8, 9, 10, 11



### DESCRIPTION

Gloves with excellent mechanical resistance parameters. Thin, made of cut-resistant knitted fabric, thanks to a special formula of polyurethane coating, provide excellent grip and flexibility. Finished with a long cuff securing the wrist. Perfectly fitted, they work well for jobs that require dexterity and object feel.

### APPLICATIONS

Ceramic and glass industry, automotive industry, all work with sharp-edged objects.



EN 388:2016+A1:2018



4X43 D

EN 407:2020



X1XXXX

EN 388:2016+A1:2018

Abrasion resistance	4
Blade cut resistance	X
Tear resistance	4
Puncture resistance	3
TDM cut resistance	D

EN 21420:2020



CAT II



EN 407:2020

Limited Flame spread	X
Contact Heat Resistance	1
Convective Heat Resistance	X
Radiant Heat Resistance	X
Resistance to Small Splashes of Molten Metal	X
Resistance to Large Quantities of Molten Metal	X

PPE regulation (EU) 2016/425 | EN 388:2016+A1:2018 Mechanical risk | EN 407:2020 Protection against thermal risks (heat and/or fire) | EN 21420:2020 General requirements for protective gloves |

**P.H.P.U. SEMEX Fertac, Huszno Sp. J.**

ul. Jagiellońska 101/105,  
 42-202 Częstochowa, Poland  
 tel.: +48 34 39 06 735  
 e-mail: bhp@semex.pl  
 www.hfsafety.pl

**KRAKOW BRANCH**

ul. Biskupińska 28, budynek X  
 30-732 Kraków  
 tel.: +48 12 390 46 00  
 e-mail: bhp.krakow@semex.pl  
 www.hfsafety.pl

