

## flexyDOTS

### TECHNICAL SPECIFICATION

Type:	knitted
Coating:	nitrile foam, nitrile dots
Material:	lycra, nylon
Cuff:	elastic
Weight:	light
Colour:	black, orange
Sizes:	6, 7, 8, 9, 10, 11, 12



### PROPERTIES

Knitted gloves (15 gauge) made of Lycra and nylon, coated with nitrile microfoam for increased resistance to grease and oils. Thanks to the nitrile spotting on palm of the hand and on the fingers, they guarantee excellent grip and anti-slip properties. The model is characterised by maximum abrasion resistance (level 4 to EN 388:2016+A1:20018) and resistance to contact heat up to 100°C.

### APPLICATION

Construction, maintenance, agriculture, logistics, vehicle mechanics, machine and tool operation.



<b>Oznaczenia:</b>	
Limited Flame Spread	X
Contact Heat	1
Convective Heat	X
Radiant Heat	X
Small Splashes of Molten Metal	X
Large Quantities of Molten Metal	X



<b>Oznaczenia:</b>	
Abrasion resistance	4
Blade cut resistance	1
Tear resistance	2
Puncture resistance	1
ISO 13997 TDM	X

PE regulation (EU) 2016/425 | This article contains the active biocidal substance: Zinc pyrithione  
 EN ISO 21420:2020 General requirements for protective gloves  
 EN 388:2016+A1:2018 Gloves protecting against mechanical risks | EN 407:2020 Gloves protecting against heat and/or flame