

armPROTECT

SPECYFIKA TECHNICZNA

Type: knitted, 15-gauge
 Material: cut-resistant fibres
 Finish: elastic cuff, thumb hole
 Colour: blue
 Sizes: width 11 cm/length 45 cm
 width 14 cm/length 45 cm



PROPERTIES

Knitted, 15-gauge seamless protective sleeve made from a fibre blend, offering high cut resistance – level C. Thanks to its lightweight, flexible design, it naturally moulds to the shape of the arm, allowing for freedom of movement and ensuring optimal performance during prolonged use. The soft, breathable fabric reduces the risk of skin irritation and promotes air circulation, significantly making them more comfortable to wear. The cuffs feature a ribbed finish with a thumb hole.

APPLICATION

The automotive industry. Glass manufacturing and processing.



EN 388:2016+A1:2018



3X4XC

EN 388:2016+A1:2018 – mechanical risk:

Abrasion resistance	3
Blade cut resistance	X
Tear resistance	4
Puncture resistance	X
ISO 13997 TDM	C

EN ISO21420:2020



EN 407:2020



X1XXXX

EN 407:2020

Limited Flame Spread	X
Contact Heat	1
Convective Heat	X
Radiant Heat	X
Small Splashes of Molten Metal	X
Large Quantities of Molten Metal	X

PPE Regulation (EU) 2016/425 | EN ISO 21420:2020 – General requirements for protective gloves | EN 388:2016+A1:2018 – Gloves protecting against mechanical risks | EN 407:2020 – Protection against high temperatures and/or flame